

THROUGH PAINT OR COATING ULTRASONIC THICKNESS GAUGE

MODEL : TM230D /TM250D

FEATURES:

- ❖ AUTOMATIC SELF CALIBRATION
- ❖ COUPLANT INDICATOR
- ❖ AUTOMATIC POWER OFF DEVICE
- ❖ HIGH-LOW LIMIT ALARM
- ❖ LCD BRIGHTNESS ADJUST
- ❖ THROUGH COATING CAPABILITY
- ❖ LOW BATTERY INDICATOR



TECHNICAL SPECIFICATIONS :

		TM230D	TM250D
MEASURING RANGE (STEEL)	STANDARD	0.8mm – 250mm Depending of the probes	
	THROUGH COATING	3mm – 18mm Depnding of the probes	
DISPLAY RESOLUTION		0.1mm or 0.01inch	0.1mm/0.01mm or 0.01inch/0.001inch
TOLERANCE		+/- 0.1mm in steel	+/- 0.025mm in steel
VELOCITY RANGE		1000-9999m/s (0.0393-0.3936inch/ μ s)	
DISPLAY TYPE		4 digital LCD with advanced backlight	
MEMORY		500 Test Values	
POWER		2 pcs. 1.5v AA Batteries	
OUTSIDE DIMENSION		149mmX73mmX32mm	
WEIGHT		160g	

STANDARD DELIVERY :

1. MAIN UNIT WITH THOUGH COATING MODE
2. STANDARD PROBE PT-08
3. COUPLANT BOTTLE
4. TWO AA SIZE 1.5V BATTERIES
5. OPERATION MANUAL
6. CARRYING CASE